

DERWENT ABSTRACT FOR: JP 09-316322 (Asahi), published 9 Dec 1997:

L2 ANSWER 3 OF 14 WPINDEX COPYRIGHT 2001 DERWENT INFORMATION LTD

ACCESSION NUMBER: 1998-082841 [08] WPINDEX

DOC. NO. CPI: C1998-028047

TITLE: Polyphenylene ether-based resin moulding - consisting of hydrogenated vinyl aromatic compound-conjugated diene compound copolymer dispersed in polyolefin.

DERWENT CLASS: A18 A25

PATENT ASSIGNEE(S): (ASAH) ASAH KASEI KOGYO KK

COUNTRY COUNT: 1

PATENT INFORMATION:

PATENT NO	KIND	DATE	WEEK	LA	PG
JP 09316322	A	19971209	(199808)*	19	<--

APPLICATION DETAILS:

PATENT NO	KIND	APPLICATION	DATE
JP 09316322	A	JP 1996-151801	19960524

PRIORITY APPLN. INFO: JP 1996-151801 , 19960524

AN 1998-082841 [08] WPINDEX

AB JP 09316322 A UPAB: 19980223

The polyolefin has: (a) a continuous phase, a homogeneous phase consisting of polyphenylene ether, or polyphenylene ether and a styrene-based resin; and (b) a dispersed phase dispersed with substantially a breadth dia. of 0.6 microns or below. The hydrogenated material of a vinyl aromatic compound-conjugated diene compound copolymer is dispersed with substantially a breadth dia. of 0.01 microns or more and 0.3 microns or below in the polyolefin. The vinyl aromatic compound-conjugated diene compound copolymer is coagulated in the outer layer of the mixed phase of the polyolefin and the hydrogenated material of the vinyl aromatic compound-conjugated diene compound copolymer. The single vinyl aromatic compound-conjugated diene compound copolymer is dispersed with substantially a breadth dia. of 0.3 microns or below. Also claimed is that a resin composition is used for forming the resin moulding consisting of: (a) 10-88 wt.-%-polyphenylene ether; (b) a 0-78 wt.-%-styrene-based resin; (c) 3-15 wt.-%-polyolefin; (d) at least one 6-20 wt.-%-block copolymer consisting of a polymer block (A) consisting mainly of at least one vinyl aromatic compound and a polymer block B consisting mainly of at least one conjugated diene compound, and selected from a block copolymer containing the 30-85 wt.-%-vinyl aromatic compound; and (e) a 3-20 wt.-% hydrogenated material of at least one block copolymer consisting of a polymer block (A) consisting mainly of at least one vinyl aromatic compound and a polymer block B consisting mainly of at least one conjugated diene compound and selected from a hydrogenated material of a block copolymer containing the 20-50 wt.-%-vinyl aromatic compound.

USE - The polyphenylene ether-based resin moulding is used in films, or sheets.

ADVANTAGE - The polyphenylene ether-based resin moulding has superior balanced heat resistance and rigidity, no peeling under severe moulding conditions, superior sliding and impact resistance.

Dwg.0/6